

Americki vodič za provodnike / American wire guide

AWG	Prečnik Diameter		Uvijanje žice, bez izolacije Turns of wire, no insulation		Površina Area	
	inč / in	mm	po inču / per in	po cm / per cm	kcmil	mm ²
0000 (4/0)	0.4600	11.684	2.17	0.856	212	107
000 (3/0)	0.4096	10.405	2.44	0.961	168	85
00 (2/0)	0.3648	9.266	2.74	1.08	133	67.4
0 (1/0)	0.3249	8.251	3.08	1.21	106	53.5
1	0.2893	7.348	3.46	1.36	83.7	42.4
2	0.2576	6.544	3.88	1.53	66.4	33.6
3	0.2294	5.827	4.36	1.72	52.6	26.7
4	0.2043	5.189	4.89	1.93	41.7	21.2
5	0.1819	4.621	5.5	2.16	33.1	16.8
6	0.162	4.115	6.17	2.43	26.3	13.3
7	0.1443	3.665	6.93	2.73	20.8	10.5
8	0.1285	3.264	7.78	3.06	16.5	8.37
9	0.1144	2.906	8.74	3.44	13.1	6.63
10	0.1019	2.588	9.81	3.86	10.4	5.26
11	0.0907	2.305	11	4.34	8.23	4.17
12	0.0808	2.053	12.4	4.87	6.53	3.31
13	0.072	1.828	13.9	5.47	5.18	2.62
14	0.0641	1.628	15.6	6.14	4.11	2.08
15	0.0571	1.45	17.5	6.9	3.26	1.65
16	0.0508	1.291	19.7	7.75	2.58	1.31
17	0.0453	1.15	22.1	8.7	2.05	1.04
18	0.0403	1.024	24.8	9.77	1.62	0.823
19	0.0359	0.912	27.9	11	1.29	0.653
20	0.032	0.812	31.3	12.3	1.02	0.518
21	0.0285	0.723	35.1	13.8	0.81	0.41
22	0.0253	0.644	39.5	15.5	0.642	0.326
23	0.0226	0.573	44.3	17.4	0.509	0.258
24	0.0201	0.511	49.7	19.6	0.404	0.205
25	0.0179	0.455	55.9	22	0.32	0.162
26	0.0159	0.405	62.7	24.7	0.254	0.129
27	0.0142	0.361	70.4	27.7	0.202	0.102
28	0.0126	0.321	79.1	31.1	0.16	0.081
29	0.0113	0.286	88.8	35	0.127	0.0642
30	0.0100	0.255	99.7	39.3	0.101	0.0509
31	0.00893	0.227	112	44.1	0.0797	0.0404
32	0.00795	0.202	126	49.5	0.0632	0.032
33	0.00708	0.18	141	55.6	0.0501	0.0254
34	0.0063	0.16	159	62.4	0.0398	0.0201
35	0.00561	0.143	178	70.1	0.0315	0.016
36	0.00500	0.127	200	78.7	0.025	0.0127
37	0.00445	0.113	225	88.4	0.0198	0.01
38	0.00397	0.101	252	99.3	0.0157	0.00797
39	0.00353	0.0897	283	111	0.0125	0.00632
40	0.00314	0.0799	318	125	0.00989	0.00501